

50591

**MATERIAL SAFETY DATA SHEET**

Vitrified Grinding Wheels

MSDS #3

**1. PRODUCT AND COMPANY IDENTIFICATION**

**Product Identity / Trade Name:** Vitrified Grinding Wheels, Including Surface Grinding Wheels (Type 1) and Mounted Points.

**Product Use:** Abrasive materials used for cutting and grinding of metals, concrete, masonry and building materials.

**Manufacturer:** United Abrasives, Inc.  
P.O. Box 75, Route 66  
Willimantic, CT 06226

**Internet:** www.unitedabrasives.com

**Information Phone:** (860) 456-7131    **Emergency Phone:** (860) 456-7131

**MSDS Date of Preparation:** November 2003

**2. COMPOSITION/INFORMATION ON INGREDIENTS**

Hazardous Component	CAS #	%
Aluminum Oxide	1344-28-1	0-80
and/or		
Silicon Carbide	409-21-2	0-80
Kaolin	1332-58-7	0-30

**3. HAZARDS IDENTIFICATION**

This product is a black, brown or reddish colored solid wheel with no odor.

**EMERGENCY OVERVIEW**

Dust may cause eye and respiratory irritation. Dust particles may cause abrasive injury to the eyes.

**4. FIRST AID MEASURES**

**Ingestion:** If grinding dust is swallowed, seek medical attention.

**Inhalation:** If overexposed to grinding dust, remove victim to fresh air and get medical attention.

**Eye Contact:** Flush eyes thoroughly with water, holding open eyelids. Get medical attention if irritation persists. Obtain immediate medical attention for foreign body in the eye.

**Skin Contact:** Wash dust from skin with soap and water. Launder contaminated clothing before reuse.

**5. FIRE FIGHTING MEASURES**

**Flash Point:** Non-Combustible

**Flammable Limits: LEL:** Not Applicable

**UEL:** Not Applicable

**Extinguishing Media:** Use any media that is appropriate for the surrounding fire.

**Special Firefighting Procedures:** None needed.

**Unusual Fire and Explosion Hazards:** This product is not combustible, however, consideration must be given to the potential fire/explosion hazards from the base material being processed. Many materials create flammable/explosive dusts or turnings when machined or ground.

**Hazardous Combustion Products:** None known.

**6. ACCIDENTAL RELEASE MEASURES**

Pick up, sweep up or vacuum and place in a container for disposal. Minimize generation of dust. Notify authorities as required by local, state and federal regulations.

**7. HANDLING AND STORAGE**

**Recommended Work Practices:** Use only with adequate ventilation. Avoid breathing dust. Wash thoroughly after handling and use, especially before eating, drinking or smoking. Refer to ANSI B7.1, Safety Requirements for the Use, Care and Protection of Abrasive Wheels for additional information. Consider potential exposure to components of the base materials or coatings being ground. Refer to OSHA's substance specific standards for additional work practice requirements where applicable.

**Storage:** Store in accordance with ANSI B7.1. Protect abrasive wheels from damage.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines:**

Hazardous Component	OSHA PEL	ACGIH TLV
Aluminum Oxide	15 mg/m <sup>3</sup> (total dust)	10 mg/m <sup>3</sup>
Silicon Carbide	15 mg/m <sup>3</sup> (total dust)	10 mg/m <sup>3</sup> (inhalable fraction)
Kaolin	15 mg/m <sup>3</sup> (total dust)	2 mg/m <sup>3</sup> (respirable)

Note: Consider also components of base materials and coatings being ground.

**Ventilation:** Use local exhaust or general ventilation as required to minimize exposure to dust and maintain the concentration of contaminants below the TLVs.

**Respiratory Protection:** Use NIOSH approved respirator if exposure limits are exceeded or where dust exposures are excessive. Consider the potential for exposure to components of the coatings or base material being ground in selecting proper respiratory protection. Refer to OSHA's specific standards for lead, cadmium, etc. where appropriate. Selection of respiratory protection depends on the contaminant type, form and concentration. Select and use respirators in accordance with OSHA 1910.134 and good industrial hygiene practice.

**Gloves:** Cloth or leather gloves recommended.

**Eye Protection:** Safety goggles or face shield over safety glasses with side shields.

**Other:** Protective clothing as needed to prevent contamination of personal clothing. Hearing protection may be required.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Boiling Point:** Not Applicable

**Solubility in Water:** Insoluble

**Specific Gravity:** Not Applicable

**Melting Point:** Not Applicable

**Appearance and Odor:** Black, gray, brown or reddish colored solid wheel, no odor.

**Vapor Pressure:** (mm Hg) Not Applicable

**Vapor Density:** (Air = 1) Not Applicable

**Evaporation Rate:** Not Applicable

**Flash Point:** Non-Combustible

**10. STABILITY AND REACTIVITY**

**Stability:** Stable

**Incompatibility:** None known.

**Hazardous Decomposition Products:** Dust from grinding could contain ingredients listed in Section 2 and other, potentially more hazardous components of the base material being ground or coatings applied to the base material.

**Hazardous Polymerization:** Will not occur.

## 11. TOXICOLOGICAL INFORMATION

### HEALTH HAZARDS:

**Ingestion:** None expected under normal use conditions. Swallowing large pieces may cause obstruction of the gastrointestinal tract.

**Inhalation:** Dust may cause respiratory irritation.

**Eye:** Dust may cause eye irritation. Dust particles may cause abrasive injury to the eyes.

**Skin:** None expected under normal use conditions. Rubbing product across the skin may cause mechanical irritation or abrasions.

**Sensitization:** This material is not known to cause sensitization.

**Chronic:** Long-term overexposure to respirable dust may cause lung damage (fibrosis) with symptoms of coughing, shortness of breath and diminished breathing capacity. Chronic effects may be aggravated by smoking. Prolonged exposure to elevated noise levels during operations may affect hearing. A greater hazard, in most cases, is the exposure to the dust/fumes from the material or paint/coatings being ground. Most of the dust generated during grinding is from the base material being ground and the potential hazard from this exposure must be evaluated.

**Carcinogenicity:** None of the components is listed as a carcinogen or potential carcinogen by OSHA, NTP or IARC.

**Medical Conditions Aggravated by Exposure:** Employees with pre-existing respiratory disease may be at risk from exposure.

### Acute Toxicity Values:

This product and its components are not acutely toxic. No specific toxicity data is available for this product or its components.

## 12. ECOLOGICAL INFORMATION

This product is not expected to be hazardous for the environment. No specific ecotoxicity data is available for this product.

## 13. DISPOSAL CONSIDERATIONS

Dispose in accordance with all applicable local, state/provincial and federal regulations. Local regulations may be more stringent than regional and national requirements. It is the responsibility of the waste generator to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

## 14. TRANSPORT INFORMATION

### DOT Hazardous Materials Description:

Proper Shipping Name: Not Regulated

UN Number: None

Hazard Class/Packing Group: None

Labels Required: None

## 15. REGULATORY INFORMATION

**SARA Section 311/312 Hazard Categories:** Not Applicable

**SARA Section 313:** This product contains the following toxic chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372 (Toxic Chemical Release Reporting):

None

**California Proposition 65:** WARNING You create dust when you cut, sand, drill or grind materials such as wood, paint, cement, masonry or metal. This dust often contains chemicals known to cause cancer, birth defects or other reproductive harm.

**Canadian WHMIS Classification:** Not a controlled product. This product meets the definition of a "manufactured article" under the WHMIS regulations.

This product has been classified under the CPR and this MSDS discloses information elements required by the CPR.

<b>16. OTHER INFORMATION</b>
------------------------------

**NFPA Hazard Rating:** Health: 1  
Fire: 0  
Reactivity: 0

**Date Previous Revision:** 11/01/00

**Date This Revision:** 11/2003

**Revision Summary:** Overall update to MSDS

**Prepared By:** Denese A. Deeds, CIH IH&SC Inc., Woodbridge, CT 06525

---

The preceding information is believed to be correct and current as of the date of preparation of this Material Safety Data Sheet. Since the use of this information and the conditions of use of this product are not within the control of United Abrasives, Inc., it is the user's obligation to assure safe use of this product.