

TRADE NAME: S-1201

50841

IV. REACTIVITY DATA

STABILITY: STABLE: X UNSTABLE:

CONDITIONS TO AVOID: Open flames, electrical arcs, and high temperature surfaces.

INCOMPATIBILITY: Strong alkalis, alkali metals, strong oxidizers, when acidic or wet - may react with aluminum and zinc.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS: Hydrogen chloride, carbon monoxide and possibly traces of phosgene.

HAZARDOUS POLYMERIZATION: Will not occur.

V. HEALTH HAZARD DATA

ROUTES OF ENTRY: INHALATION - YES SKIN - YES INGESTION - YES

EFFECTS OF ACUTE OVEREXPOSURE: Material is an eye and skin irritant. Excessive vapor inhalation will lead to central nervous system depression. Harmful or fatal if swallowed.

CHRONIC OVEREXPOSURE: Material may defat the skin on repeated exposure leading to dermatitis. Studies have shown that chronic overexposure may lead to damage to the liver and/or kidneys.

CARCINOGENICITY: NTP: NO IARC: NO OSHA: NO

-THIS BLEND CONTAINS NO LISTED CARCINOGENS-

SIGNS & SYMPTOMS OF EXPOSURE: The signs of central nervous system depression begin with headache, dizziness and apparent intoxication, and progress through loss of consciousness.

MEDICAL CONDITIONS AGGRAVATED BY EXPOSURE: Skin contact can aggravate existing dermatitis.

EMERGENCY & FIRST AID PROCEDURE:

EYE CONTACT - rinse with water for 15 minutes. If irritation persists call a physician.

SKIN CONTACT - wash with plenty of soap and water. Wash contaminated clothing before reuse. EXCESSIVE VAPOR INHALATION - remove victim to fresh air and restore breathing if necessary. Call a physician if there are signs of breathing difficulties.

IF SWALLOWED - do not induce vomiting, call a physician immediately with the listing of materials on this sheet.

VI. PRECAUTIONS FOR SAFE HANDLING & USE

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Stop spill at the source, dike the area and contain the flow mop up or absorb and place in suitable container. Notify proper authorities if an RD was involved.

WASTE DISPOSAL METHOD: As directed by local and federal pollution laws.

PRECAUTIONS TO BE TAKEN IN HANDLING & STORAGE: Avoid free fall of liquid, ground containers when pouring. Store and use below 120°F and away from direct heat and open flame.

VII. CONTROL MEASURES

RESPIRATORY PROTECTION: Organic cartridge type respirator if ventilation or other mechanical means cannot keep air below TLV.

VENTILATION: Local exhaust is preferable, but any mechanical means that will keep vapors below limits is acceptable.

PROTECTIVE GLOVES: Recommended - must not dissolve in solvents.

OTHER PROTECTIVE CLOTHING OR EQUIPMENT: Chemical goggles and apron are recommended if splashing is possible. An eye wash and safety shower should be available.

WORK/HYGIENIC PRACTICES: Avoid breathing vapor or spray mist. Wash hands thoroughly after contact and before breaks or meals.

VIII. LISTED MATERIALS

As per the requirements of 40 CFR 372.45, the following components of this blend are listed in Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986.

MATERIAL	CAS #	MAXIMUM % BY WT
TRICHLOROETHYLENE	79-01-6	100

The act also requires that this notice accompany the MSDS in all redistributions and not be detached or omitted from future copies.

Print Date: 04/11/97

Last Revision: 01/01/95